## NSN 5310-01-390-2820

Plate Self-locking Nut - Page 1 of 2

**Thread Class:** 

3b

View Online at https://aerobasegroup.com/nsn/5310-01-390-2820



## **Thread Direction: Right-hand** Locking Feature: Prevailing torque all metal design **Overall Height:** Between 0.391 inches and 0.416 inches Mounting Hole Diameter: Between 0.098 inches and 0.103 inches Nut Style: Plate Nut Length: 0.948 inches Nut Height: 0.250 inches **Plate Thickness:** 0.032 inches Plate Width: Between 0.391 inches and 0.416 inches **Nut Mounting Provision:** Gripping prongs Mounting Hole Arrangement Style: 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.686 inches and 0.690 inches **Tempurature Rating:** 800.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): Thread Size: 0.190 inches Material: Iron alloy 660 **Material Specification:**

Ams5525 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single

material response

32

## NSN 5310-01-390-2820

Plate Self-locking Nut - Page 2 of 2

---



**Precious Material And Location:** On nut silver **Precious Material:** Silver Surface Treatment: Silver Surface Treatment Specification: Ams 2410 assn standard single treatment response **Specification Data:** 80205-nas1773 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0