

View Online at <https://aerobasegroup.com/nsn/5310-01-391-9111>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Small End Diameter:**

Between 0.851 inches and 0.856 inches

**Drive Point Depth:**

Between 0.050 inches and 0.060 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 0.938 inches and 0.948 inches

**Nut Thickness:**

Between 0.219 inches and 0.224 inches

**Drive Point Width:**

Between 0.125 inches and 0.135 inches

**Undercut Thickness:**

Between 0.100 inches and 0.105 inches

**Drive Point Quantity:**

8

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

Between 26.0 rockwell c and 33.0 rockwell c

**Thread Size:**

0.664 inches

**Countersink Angle:**

89.5 degrees nut and 90.5 degrees nut

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2cl2 federal specification single treatment response

**Specification Data:**

80205-nas1493 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6758 spec.