NSN 5310-01-408-3390

Spring Tension Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-408-3390

		_					
Hol	_	ı	12	m	0	ŀ۵	r-

Between 3.2 millimeters and 3.5 millimeters

Outside Diameter:

Between 5.625 millimeters and 6.375 millimeters

Overall Height:

Between 0.65 millimeters and 1.30 millimeters

Material Thickness:

Between 0.35 millimeters and 0.45 millimeters

Hardness Rating:

Between 82.0 rockwell superficial 15-n and 85.5 rockwell superficial 15-n

Material:

Steel comp 1050 or steel comp 1055 or steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 1086 or steel comp 1095

Material Specification:

Astm a682 assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response or mil-c-81562, type 2, cl 2 military specification single treatment response

Style Designator:

Spring tension

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A022b0

Mil-std (military Standard):

Mil-c-81562 spec.