NSN 5310-01-414-7132

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-414-7132 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Washer Outside Diameter:** 1.310 inches **Counterbore Diameter:** 0.435 inches nut and 0.445 inches nut **Overall Height:** Between 0.650 inches and 0.670 inches **Nut Style:** Flat with turned up edge **Nut Counterbore Depth:** 0.090 inches nut and 0.105 inches nut Width Across Flats: Between 0.865 inches and 0.977 inches **Thread Series:** Unif Thready Qty Per Inch (tpi): 16 Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Thread Size:** 0.750 inches Material: Steel comp 4340 nut or steel comp 8740 nut **Material Specification:** Mil-s-5000 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2, cl 3 federal specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A021a0

NSN 5310-01-414-7132

Assembled Washer Self-locking Nut - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.