

View Online at <https://aerobasegroup.com/nsn/5310-01-423-3733>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.234 inches first end and 0.270 inches first end

Overall Height:

0.250 inches

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.948 inches

Nut Height:

0.250 inches

Plate Thickness:

0.032 inches

Plate Width:

Between 0.290 inches and 0.416 inches

Nut Counterbore Depth:

0.032 inches first end

Nut Mounting Provision:

Welding projections

Mounting Provision Location:

Opposite nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.239 inches and 0.349 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Tempurature Rating:

800.0 degrees fahrenheit

Thread Series:

Unc

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Hardness Rating:

49.0 rockwell c

Thread Size:

0.164 inches

Material:

Iron alloy 660

Material Specification:

Ams 5525 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Precious Material And Location:

silver

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-n-25027 spec.