# NSN 5310-01-423-4057

Plate Self-locking Nut - Page 1 of 2





Thread Class:

3b

**Thread Direction:** 

**Right-hand** 

## Locking Feature:

Prevailing torque all metal design

## Counterbore Diameter:

0.194 inches first end

Lubrication:

Dry film lubricant

#### Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate (floating)

Nut Length:

## 0.948 inches

Nut Height:

0.299 inches

Plate Thickness:

Between 0.028 inches and 0.036 inches

Plate Width:

0.454 inches

#### Nut Counterbore Depth:

0.125 inches first end

#### **Nut Mounting Provision:**

Straight holes

#### Mounting Hole Arrangement Style:

2 holes

#### Distance From Aperture Center To Mounting Hole Center:

Between 0.339 inches and 0.349 inches

#### Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

**Thread Series:** 

Unjf

**Features Provided:** 

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Iron alloy 660 shell

## NSN 5310-01-423-4057

Plate Self-locking Nut - Page 2 of 2



## Material Specification:

Ams 5525 assn standard single material response shell or ams 5732 assn standard single material response shell

Surface Treatment:

Passivate shell

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shell

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0