## NSN 5310-01-425-4902

Key Washer - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5510-01-425-4902
Hole Diameter:
Between 5.655 inches and 5.675 inches
Outside Diameter:
Between 6.325 inches and 6.345 inches
External Straight Key Width:
Between 0.270 inches and 0.290 inches
Internal Straight Key Width:
Between 0.480 inches and 0.490 inches
Distance From Centerline To Top Of Internal Key:
Between 2.650 inches and 2.660 inches
Overall Distance Including Keys:
Between 6.640 inches and 6.660 inches
External Key Quantity:
4
Internal Key Quantity:
2
Material Thickness:
Between 0.046 inches and 0.054 inches
End Application:
Preprovisioning support navicp is poe
Hardness Rating:
Between 32.0 rockwell c and 36.0 rockwell c
Surface Finish:
63.0 microinches top
Special Features:
Internal keys 180.0 degrees apart offset 27 degrees from center line of external keys
Material:
Steel comp 4130 or steel comp 4340
Material Specification:
Mil-s-18729 military specification 1st material response or ams 6415 assn standard 2nd material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
D0d-p-16232, ty z, cl 4 military specification single treatment response
Style Designator:
Key
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5310-01-425-4902

Key Washer - Page 2 of 2



Fiig:

A022b0

Mil-std (military Standard):

Mil-s-18729 spec.