

NSN 5310-01-435-2372 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-435-2372 **Thread Class:** 2b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.040 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.418 inches and 0.440 inches **Head Minor Diameter:** 0.350 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.325 inches and 0.327 inches **Nut Length:** Between 0.827 inches and 0.857 inches **Nut Grip Range:** +0.340/+0.400 inches **Shank End Type:** Closed **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf

Thready Qty Per Inch (tpi):

28

**Thread Size:** 

0.250 inches

**Head Major Countersink Angle:** 

76.0 degrees

**Head Minor Countersink Angle:** 

60.0 degrees

Material:

Steel comp 304 and steel comp 305

**Material Specification:** 

Qq-s-763 cond a federal specification all material responses

## NSN 5310-01-435-2372

Blind Rivet Self-locking Nut - Page 2 of 2



## **Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 type 2, class 2 federal specification single treatment response

**Specification Data:** 

80205-nas1735 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0