## NSN 5310-01-435-6426

Gang Channel Self-locking Nut Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-435-6426

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque all metal design   |
| Counterbore Diameter:  |
| 0.254 inches channel   |
| Lubrication:   |
| Dry film lubricant   |
| Overall Length:  |
| 72.000 inches  |
| Overall Width:   |
| 0.574 inches   |
| Nut Style:   |
| Gang channel, self locking   |
| Channel Style:   |
| Straight type  |
| Assemblyheight:  |
| 0.470 inches   |
| Nut Spacing:   |
| Between 1.146 inches and 1.166 inches  |
| Nut Counterbore Depth:   |
| 0.070 inches nut   |
| Nut Quantity:  |
| 62   |
| Thread Series:   |
| Unjf   |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Thread Size:   |
| 0.250 inches   |
| Special Features:  |
| Channel anodized before sealer coating.  |
| Material:  |
| Steel comp 302 clip  |
| Material Specification:  |
| Qq-a-250 federal specification single material response channel or qq-a-200 federal specification single material response channel |
| Surface Treatment:   |
| Passivate nut  |
| Surface Treatment Specification:   |

Qq-p-35 federal specification single treatment response nut

## NSN 5310-01-435-6426

Gang Channel Self-locking Nut Assembly - Page 2 of 2



| Shelf Life:                  |
|------------------------------|
| N/a                          |
| Unit Of Measure:             |
|                              |
| Demilitarization:            |
| No                           |
| Fiig:                        |
| A021a0                       |
| Mil-std (military Standard): |

Mil-a-8625 spec.