

View Online at <https://aerobasegroup.com/nsn/5310-01-436-6488>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.254 inches first end

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate (floating)

**Nut Length:**

1.292 inches

**Nut Height:**

0.662 inches

**Plate Thickness:**

0.032 inches

**Plate Width:**

0.516 inches

**Nut Counterbore Depth:**

0.438 inches first end

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.495 inches and 0.505 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.998 inches and 1.002 inches

**End Application:**

W/s: helicopter, lamps mark iii, sh-60b; aircraft, orion p-3; aircraft, viking s-3b; helicopter, seahawk, h-60

**Thread Series:**

Unjf

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0