Hexagon Extended Washer Self-locking Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-461-8049

2b Thread Direction: Right-hand Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.686 inches and 0.706 inches Overall Height: Between 0.281 inches and 0.304 inches Hasher Thickness: Between 0.025 inches and 0.038 inches
Right-hand Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.686 inches and 0.706 inches Overall Height: Between 0.281 inches and 0.304 inches Washer Thickness:
Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.686 inches and 0.706 inches Overall Height: Between 0.281 inches and 0.304 inches Washer Thickness:
Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.686 inches and 0.706 inches Overall Height: Between 0.281 inches and 0.304 inches Washer Thickness:
Prevailing torque all metal design <b>Washer Outside Diameter:</b> Between 0.686 inches and 0.706 inches <b>Overall Height:</b> Between 0.281 inches and 0.304 inches <b>Washer Thickness:</b>
Between 0.686 inches and 0.706 inches Overall Height: Between 0.281 inches and 0.304 inches Washer Thickness:
Overall Height: Between 0.281 inches and 0.304 inches Washer Thickness:
Between 0.281 inches and 0.304 inches Washer Thickness:
Washer Thickness:
Between 0.025 inches and 0.038 inches
Width Across Flats:
Between 0.489 inches and 0.500 inches
Thread Series:
Unc
Thready Qty Per Inch (tpi):
18
Thread Size:
0.312 inches
Product Name:
Serrated flanged hex lock nuts
Special Features:
24 flange serrations equally spaced/serr.Height 0.009/serr.Length 0.051
Material:
Steel comp 1010
Surface Treatment:
Zinc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0