Hexagon Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-462-6244

2b Thread Direction: Right-hand Locking Feature: Prevailing torque all metal design Lubrication: Dry film lubricant Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches End Application:
Right-hand Locking Feature: Prevailing torque all metal design Lubrication: Dry film lubricant Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Locking Feature: Prevailing torque all metal design Lubrication: Dry film lubricant Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Prevailing torque all metal design Lubrication: Dry film lubricant Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Lubrication: Dry film lubricant Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Dry film lubricant Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Nut Style: Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Hexagon Nut Height: Between 0.724 inches and 0.922 inches
Nut Height: Between 0.724 inches and 0.922 inches
Between 0.724 inches and 0.922 inches
End Application:
Nsn 4210-01-486-1035 tfft (tactical fire fighting truck)
Width Across Flats:
Between 1.269 inches and 1.314 inches
Tempurature Rating:
250.0 degrees fahrenheit
Thread Series:
Unc
Thready Qty Per Inch (tpi):
9
Thread Size:
0.875 inches
Bearing Surface Type:
Chamfered or washer faced
Bearing Surface Finish:
125.0 microinches
Material:
Steel
Material Specification:
Sae j995, gr 5 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 or 3 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## **NSN 5310-01-462-6244** Hexagon Self-locking Nut - Page 2 of 2

Fiig: A021a0

