

View Online at <https://aerobasegroup.com/nsn/5310-01-464-7100>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.206 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate (floating)

**Nut Length:**

0.948 inches

**Nut Height:**

0.171 inches

**Plate Thickness:**

0.047 inches

**Plate Width:**

Between 0.240 inches and 0.265 inches

**Nut Counterbore Depth:**

0.124 inches nut

**Nut Mounting Provision:**

Dimpled holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.342 inches and 0.346 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.686 inches and 0.708 inches

**Temperature Rating:**

800.0 degrees fahrenheit

**Thread Series:**

Unjc

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5525 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Specification Data:**

80205-nas1770 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0