

View Online at https://aerobasegroup.com/nsn/5310-01-468-1983

| Thread Class: |
|---|
| |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.194 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 71.955 inches |
| Overall Width: |
| 0.452 inches |
| Nut Style: |
| Gang channel, self locking |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.566 inches |
| Channel Height: |
| 0.250 inches |
| Nut Spacing: |
| 0.875 inches |
| Nut Counterbore Depth: |
| 0.384 inches nut |
| End Application: |
| C17a aircraft |
| Tempurature Rating: |
| 350.0 degrees fahrenheit |
| Nut Quantity: |
| 4 |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.190 inches |
| Material: |
| Stainless steel nut |
| Material Specification: |
| Qq-a-250/13, 7075-t6 federal specification single material response channel |

NSN 5310-01-468-1983

Gang Channel Self-locking Nut Assembly - Page 2 of 2



Surface Treatment:

Passivate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.