

View Online at <https://aerobasegroup.com/nsn/5310-01-473-1810>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Soluble lubricant

Nut Height:

Between 0.240 inches and 0.328 inches

End Application:

6115-01-317-2139

Width Across Flats:

Between 0.430 inches and 0.439 inches

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Bearing Surface Type:

Chamfered or washer faced

Bearing Surface Finish:

125.0 microinches

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1018 or steel comp 1021 or steel comp 1022 or steel comp 1030 or steel comp 1035 or steel comp 1045 or steel comp 1110 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1213 or steel comp 8740

Material Specification:

Astm a29 assn standard 1st material response or ams 5050 assn standard 2nd material response or ams 5060 assn standard 3rd material response or ams 5069 assn standard 4th material response or ams 5070 assn standard 5th material response or ams 5080 assn standard 5th material response or ams 5022 assn standard 7th material response or ams 5024 assn standard 8th material response or ams 5020 assn standard 9th material response or ams 6322 assn standard 10th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No