## NSN 5310-01-473-1810



Hexagon Self-locking Nut - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5310-01-473-1810 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Soluble lubricant **Nut Height:** Between 0.240 inches and 0.328 inches **End Application:** 6115-01-317-2139 Width Across Flats: Between 0.430 inches and 0.439 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Bearing Surface Type:** Chamfered or washer faced **Bearing Surface Finish:** 125.0 microinches Material: Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1018 or steel comp 1021 or steel comp 1022 or steel comp 1030 or steel comp 1035 or steel comp 1045 or steel comp 1110 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1213 or steel comp 8740 **Material Specification:** Astm a29 assn standard 1st material response or ams 5050 assn standard 2nd material response or ams 5060 assn standard 3rd material response or ams 5069 assn standard 4th material response or ams 5070 assn standard 5th material response or ams 5080 assn standard

5th material response or ams 5022 assn standard 7th material response or ams 5024 assn standard 8th material response or ams 5020 assn standard 9th material response or ams 6322 assn standard 10th material response

## **Surface Treatment:**

Cadmium

## **Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization: