NSN 5310-01-477-6445

Assembled Washer Self-locking Nut - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5310-01-477-6445 |
|---|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 0.380 inches |
| Counterbore Diameter: |
| 0.211 inches nut and 0.221 inches nut |
| Lubrication: |
| Soluble lubricant |
| Overall Height: |
| 0.233 inches |
| Nut Style: |
| Flat with turned up edge |
| Width Across Flats: |
| Between 0.213 inches and 0.221 inches |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| Between 36.0 rockwell c and 40.0 rockwell c |
| Thread Size: |
| 0.190 inches |
| Product Name: |
| Nut, self-locking, captive washer |
| Material: |
| Steel comp 8740 |
| Surface Treatment: |
| Cadmium |
| Specification Data: |
| 80205-nas1726 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5310-01-477-6445

Assembled Washer Self-locking Nut - Page 2 of 2



Fiig:

A021a0