NSN 5310-01-482-6452

Hexagon Extended Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-482-6452

Thread Class:
3b
Thread Direction:
Right-hand
Locking Feature:
Prevailing torque with metallic insert
Washer Outside Diameter:
Between 0.725 inches and 0.770 inches
Lubrication:
Soluble lubricant
Overall Height:
Between 0.548 inches and 0.578 inches
Nut Style:
Castellated hexagon
Washer Thickness:
0.070 inches
End Application:
V-22 aircraft
Width Across Flats:
Between 0.554 inches and 0.566 inches
Tempurature Rating:
450.0 degrees fahrenheit
Thread Series:
Unjf
Thready Qty Per Inch (tpi):
20
Thread Size:
0.500 inches
Criticality Code Justification:
Agav
Product Name:
Nut, self-locking, lightweight, castellaed, 450 degree f
Special Features:
Reference cotterpin size - 3/32 inches (0.09375); navy - nut, self-locking, aircraft
Material:
Steel comp 1035 or steel comp 1042 or steel comp 1050 or steel comp 1137 or steel comp 11137 or steel comp 4027 or steel comp 4037
or steel comp 8740
Material Specification:
Ams 5080 assn standard 1st material response or qq-s-700 federal specification 2nd material response or ams 5085 assn standard 3rd
material response or ams 5024 assn standard 4th material response or ams 5020 assn standard 5th material response or astm a322 uns
g40270 assn standard 6th material response or astm a322, uns g40370 assn standard 7th material response or astm 331, uns g40370
assn standard 7th material response or astm a519, uns g40370 assn standard 7th material response or astm a547, uns g40370 assn

standard 7th material response or ams 6322, uns g87400 assn standard 8th material response or ams 6323, uns g87400 assn standard 8th material response or ams 6327, uns g87400 assn standard 8th material response or ams 6327, uns87400 assn standard 8th material

ame62E9 upg g97400 again standard 9th material response

NSN 5310-01-482-6452

Hexagon Extended Washer Self-locking Nut - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

tion:

No

Fiig:

A021a0