NSN 5310-01-485-4529

Hexagon Plain Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-485-4529

Interactions: By Thread Direction: Right-hand Nut Syle: Hexagon Nut Height: Between 0.299 inches and 0.257 inches End Application: Interconnection With Across Flats: Between 0.607 inches and 0.625 inches Enterd Series: Unc Thread Stree: 0.375 inches Bearing Surface Type: Chamfered Special Features: Wagnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 315 or steel comp 317 or steel c	Thread Class:
Fread Direction:Right-handRight-handNut Style:HasgonNut Height:Batwano 239 inches and 0.257 inchesEnd Application:InterconnectionWith Across Flas:Control SciencesThread Series:UncDaread Series:Control SciencesBarsen SciencesDaread Stries:Control StrictSciencesControl StrictBearing Surface Type:Control StrictStrict SciencesSciencesStrict SciencesSciencesSciencesStrict SciencesSciencesStrict SciencesSciencesSciencesSciencesSciencesStrict SciencesStrict SciencesSciencesStrict SciencesSciencesSciencesStrict Sciences <tr< td=""><td></td></tr<>	
Right-hand Nut Style: Hexagon Nut Height: Between 0.239 inches and 0.257 inches End Application: Interconnection With Across Flats: Between 0.807 inches and 0.625 inches Thread Series: Unc Thread Series: 0.375 inches Angelication: Name Other Paready Style Part Inch (tpl): 16 Thread Stiz: 0.375 inches Beating Surface Type: Chamfered Special Features: Naterial: Stal comp 302 or stel comp 303 or stel comp 304 or stel comp 305 or stel comp 317 or stel comp 318 or stel	
Nut Sigie: Hexagon Nut Height: Betwen 0.239 Inches and 0.257 Inches Fachaplication: Interconnection With Across Flats: Betwen 0.607 Inches and 0.625 Inches Toread Series: Unc Thready Oty Per Inch (tpi): 10 Thready Oty Per Inch (tpi): 13 Charles: 0.375 Inches Barling Surface Type: 13 Pacified Special Features: Nackite permeability of 2.00 Material: Stearong 302 or steel comp 303 or steel comp 304 or steel comp 315 or steel comp 317 or steel comp 318 or steel comp 317 or steel comp 318 or steel comp 318 or steel comp 318 or steel comp 318 or steel comp 319 or steel comp 317 or steel comp 318 or s	
Heagon Nut Height: Between 0.239 inches and 0.257 inches End Application: Interconnection Width Across Flats: Between 0.607 inches and 0.625 inches Thread Series: Unc Thready Oty Per Inch (ipi): 16 Thread Size: 0.375 inches Betweine Descention Martinet Special Features: Nagnetic permeability of 2.00 Marter Stelecomp 302 or stele comp 303 or stele comp 305 or stele comp 316 or stele comp 317 or stele comp 318 o	
Nur Height: Between 0.239 inches and 0.257 inches End Application: Interconnection With Across Flats: Between 0.607 inches and 0.625 inches Thread Series: Unc Thready Outp Per Inch (tpi): 16 Thready State: 0.375 inches Bearing Surface Type: Chamfered Special Features: Nagnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 or steel comp 317 or steel comp 302 Nickel Sheft If: Nickel Since Nickel Sheft If: Nickel Filt If: Nickel Sheft If:	
Petween 0.239 inches and 0.257 inches End Application: Interconnection With Across Flats: Between 0.607 inches and 0.625 inches Thread Series: Unc Thready Qty Per Inch (tpi): 16 Thready State: 0.375 inches Bearing Surface Type: Chamfered Special Features: Nagnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 or steel comp 317 or steel comp 304 Nickel Sheft Life: Nickel Sheft Life: Nickel Sheft Life: Nickel File: Nickel Sheft Life: Nickel File: Nickel Sheft Life: Nickel Sheft Life: Nickel Sheft Life: Sheft Life: Sheft Life: Sheft Life: Sheft Life: Sheft Life: Sheit Life: <td< td=""><td>-</td></td<>	-
Fad Application: Interconnection With Across Flats: Between 0.607 inches and 0.625 inches Thread Series: Unc Thready Oxy Per Inch (tpi): 16 Thread Size: 0.375 inches Bearing Surface Type: Other Partice Type: Other Bayesine Series: Namered: Storage Composition Series: Namered: Storage Composition Series: Storage Composition Series: Namered: Storage Composition Series: Namered: Storage Composition Series: Storage Composition Series: Storage Composition Series: Namered: Storage Composition Series: Namered: Storage Composition Series: Namered: Storage Composition Series: Namered: Storage Composition Series: Storage Composition Series: Namered: Storage Composition Series: Namered: Storage Composition Series: <	
Interconnection Vidth Across Flats: Exterent 0.607 inches and 0.625 inches Thread Series: Unc Thready Quy Per Inch (tpi): 16 Thread Size: 0.375 inches Berlender Marker Paring Surface Type: Other Marker Paring Surface Type:	
With Across Flats:Between 0.607 inches and 0.625 inchesForead Series:UncToready dy Per Inch (tpi):1650 and 0.625 inchesBearing Surface Type:ChamferedSpecial Features:Nagnetic permeability of 2.00Material:Stel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 303NickelSheff Life:NickelSinder Surface Type:NickelSinder Surface Type:NickelSheff Life:NickelFinder Surface Type:Finder Surface Type:Sinder Surface Type:NickelFinder Surface Type:Sinder Surface Type: <tr< td=""><td></td></tr<>	
Between 0.607 inches and 0.625 inches Tread Series: Unc Thready Cyp Per Inch (tpi): 16 Thread Size: 0.375 inches Bearing Surface Type: Chamfered Special Features: Nagnetic permeability of 2.00 Material: Stel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 304 or steel comp 316 or steel comp 317 or steel comp 304 or steel comp 316 or steel comp 316 or steel comp 317 or steel comp 317 Nickel Sheft Life: Nick Grid Measure: Init of Measure: Init of Measure: Init of Measure: Fomilitarization: No Fig:	
Iread Series:UncInready Qty Per Inch (tpi):16Thread Size:0.375 inchesBearing Surface Type:ChamferedParela Features:Magnetic permeability of 2.00Material:Stel comp 302 or steel comp 304 or steel comp 305 or steel comp 317 or steel comp 347NickelParlet I-Ife:NickelInter Company:Material:NickelDenilitarization:Ini Company:Fig:NickelFig:NoNoNoFig:No <t< td=""><td></td></t<>	
Unc Thready Qty Per Inch (tpi): 16 Thread Size: 0.375 inches Barring Surface Type: Chamfered Pareial Features: Magnetic permeability of 2.00 Material: Stel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 304 Nickel Furface Treatment: Nickel Intif Cheasure: I	
Hready Qty Per Inch (tpi):1616Fread Size:0.375 inchesBaring Surface Type:ChamferedSpecial Features:Magnetic permeability of 2.00Material:Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 304NickelSheft Life:NickelInit of Measure:-Pomilitarization:NoFig:	
16 Thread Size: 0.375 inches Baring Surface Type: Chamfered Special Features: Magnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 or steel comp 317 or steel comp 317 Stele Comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 317 Nickel Sheft Life: N/a Inf Of Measure: - Pomilitarization: No Fig:	
Thread Size: 0.375 inches Baring Surface Type: Chamfered Poerial Features: Magnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Shelf Life: Na Inti Of Measure: Pointiatrization: Na Fig:	
 0.375 inches Bearing Surface Type: Chamfered Special Features: Magnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Shelf Life: N/a Inti Of Measure: Imiliarization: No Fig: 	
Bearing Surface Type: Chamfered Special Features: Magnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Sheft Life: N/a Dutt Of Measure: - Pomilitarization: No Fig:	
Chamfered Special Features: Magnetic permeability of 2.00 Material: Stel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Sheff Life: N/a Unit Of Measure: Pomilitarization: No Fig:	
Special Features: Magnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 344 Surface Treatment: Nickel Shelf Life: N/a Unit Of Measure: Pomilitarization: No Fig:	
Magnetic permeability of 2.00 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 317 or steel comp 347 Surface Treatment: Nickel Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Surface Treatment:NickelShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Nickel Shelf Life: N/a Unit Of Measure: Pomilitarization: No	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A021a0	
	A021a0