

View Online at <https://aerobasegroup.com/nsn/5310-01-496-5155>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Head Style:**

Flat

**Head Diameter:**

Between 0.650 inches and 0.680 inches

**Head Height:**

0.062 inches

**Nut Style:**

Blind rivet w/smooth round shank

**Nut Diameter:**

Between 0.409 inches and 0.413 inches

**Nut Length:**

Between 0.735 inches and 0.765 inches

**Err Default:**

+0.030/+0.125 inches

**Shank End Type:**

Open

**End Application:**

Truck, forklift, 4000lb

**Thread Series:**

Unc

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.3125 inches

**Special Features:**

Keyway depth is 0.097 min-0.102 max; keyway diameter is 0.128 min-0.131max

**Material:**

Aluminum alloy 6053

**Material Specification:**

Astm-b316, uns a96053 assn standard 1st material response or qq-a-430, uns a96053 federal specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-a-8625 spec.