

View Online at <https://aerobasegroup.com/nsn/5310-01-496-5155>

Thread Class:

3b

Thread Direction:

Right-hand

Head Style:

Flat

Head Diameter:

Between 0.650 inches and 0.680 inches

Head Height:

0.062 inches

Nut Style:

Blind rivet w/smooth round shank

Nut Diameter:

Between 0.409 inches and 0.413 inches

Nut Length:

Between 0.735 inches and 0.765 inches

Err Default:

+0.030/+0.125 inches

Shank End Type:

Open

End Application:

Truck, forklift, 4000lb

Thread Series:

Unc

Thready Qty Per Inch (tpi):

18

Thread Size:

0.3125 inches

Special Features:

Keyway depth is 0.097 min-0.102 max; keyway diameter is 0.128 min-0.131max

Material:

Aluminum alloy 6053

Material Specification:

Astm-b316, uns a96053 assn standard 1st material response or qq-a-430, uns a96053 federal specification 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.