NSN 5310-01-496-5155

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-496-5155 **Thread Class: Thread Direction:** Right-hand **Head Style:** Flat **Head Diameter:** Between 0.650 inches and 0.680 inches **Head Height:** 0.062 inches **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.409 inches and 0.413 inches **Nut Length:** Between 0.735 inches and 0.765 inches **Err Default:** +0.030/+0.125 inches **Shank End Type:** Open **End Application:** Truck, forklift, 4000lb **Thread Series:** Unc Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.3125 inches **Special Features:** Keyway depth is 0.097 min-0.102 max; keyway diameter is 0.128 min-0.131 max Material: Aluminum alloy 6053 **Material Specification:** Astm-b316, uns a96053 assn standard 1st material response or qq-a-430, uns a96053 federal specification 2nd material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response

N/a **Uni**t

Shelf Life:

Unit Of Measure:

NSN 5310-01-496-5155

Blind Rivet Plain Nut - Page 2 of 2



Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.