## NSN 5310-01-496-5155

Blind Rivet Plain Nut - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5310-01-496-5155

Thread Cla	ass:
3b	
Thread Di	rection:
Right-hand	
Head Style	e:
Flat	
Head Dian	neter:
Between 0	.650 inches and 0.680 inches
Head Heig	yht:
0.062 inche	es
Nut Style:	
Blind rivet	w/smooth round shank
Nut Diame	eter:
Between 0	.409 inches and 0.413 inches
Nut Lengt	h:
Between 0	.735 inches and 0.765 inches
Err Defaul	lt:
+0.030/+0.	125 inches
Shank End	d Type:
Open	
End Appli	cation:
Truck, forl	klift, 4000lb
Thread Se	eries:
Unc	
Thready G	Rty Per Inch (tpi):
18	
Thread Siz	ze:
0.3125 incl	hes
Special Fe	eatures:
Keyway de	epth is 0.097 min-0.102 max; keyway diameter is 0.128 min-0.131max
Material:	
Aluminum	alloy 6053
Material S	pecification:
Astm-b316	6, uns a96053 assn standard 1st material response or qq-a-430, uns a96053 federal specification 2nd material response
Surface Tr	reatment:
Anodize	
Surface Ti	reatment Specification:
Mil-a-8625	i, type 2 military specification single treatment response
Shelf Life:	
N/a	
Unit Of Me	easure:

## NSN 5310-01-496-5155

Blind Rivet Plain Nut - Page 2 of 2

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.

