NSN 5310-01-502-8956

Assembled Washer Self-locking Nut - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5310-01-502-8956 |
|--|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 0.380 inches |
| Lubrication: |
| Dry film lubricant |
| Overall Height: |
| 0.233 inches |
| Nut Style: |
| Flat with turned up edge |
| Width Across Flats: |
| Between 0.213 inches and 0.221 inches |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.190 inches |
| Material: |
| Titanium alloy uns r56400 nut |
| Material Specification: |
| Ams4928 assn standard single material response nut |
| Surface Treatment: |
| Passivate washer |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response washer |
| Specification Data: |
| Nas1726 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A021a0