NSN 5310-01-507-2166

Sleeve Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-507-2166

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.311 inches |
| Lubrication: |
| Dry film lubricant |
| Flange Diameter: |
| Between 0.306 inches and 0.313 inches |
| Flange Thickness: |
| Between 0.035 inches and 0.065 inches |
| Nut Style: |
| Sleeve |
| Nut Diameter: |
| Between 0.185 inches and 0.186 inches |
| Nut Length: |
| Between 0.426 inches and 0.431 inches |
| End Application: |
| C-17a aircraft |
| Cross-sectional Shape: |
| Round nut |
| Tempurature Rating: |
| Not rated |
| Thread Series: |
| Unjc |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| Not rated |
| Thread Size: |
| 0.138 inches |
| Material: |
| Iron alloy 660 nut |
| Material Specification: |
| Ams 5737 assn standard single material response nut |
| Surface Treatment: |
| Passivate nut |
| Surface Treatment Specification: |
| Ams-qq-p-35, type ii assn standard single treatment response nut |
| Shelf Life: |
| N/o |

NSN 5310-01-507-2166

Sleeve Nut - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A021a0