

View Online at https://aerobasegroup.com/nsn/5310-01-507-3019

| Thread Class:   |
|---|
| 3b  |
| Thread Direction:   |
| Right-hand  |
| Locking Feature:  |
| Free-running all metal design   |
| Lubrication:  |
| Dry film lubricant  |
| Overall Length:   |
| Between 5.990 inches and 6.010 inches   |
| Overall Width:  |
| 0.416 inches  |
| Nut Style:  |
| A20 gang channel, self locking  |
| Channel Style:  |
| Straight type   |
| Assemblyheight:   |
| 0.250 inches  |
| Channel Height:   |
| 0.250 inches  |
| Nut Spacing:  |
| 2.000 inches  |
| End Application:  |
| 1520-01-088-3669; helicopter, cargo-transport; w/s: helicopter, chinook ch-47   |
| Tempurature Rating:   |
| 250.0 degrees fahrenheit  |
| Nut Quantity:   |
| 3   |
| Thread Series:  |
| Unjf  |
| Features Provided:  |
| Floating nut  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Hardness Rating:  |
| 49.0 rockwell c   |
| Thread Size:  |
| 0.190 inches  |
| Material:   |
| Steel comp 1035 or steel comp 1040 or steel comp 1050 or steel comp 1042 or steel comp 4130 or steel comp 4340 or steel comp 8740 |
| nut   |
| Material Specification:   |

## Material Specification:

Qq-s-635, astm a29 federal specification 1st material response nut



Surface Treatment:

Cadmium or chromate nut

## Surface Treatment Specification:

Qq-p-416 federal specification single treatment response channel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.