## NSN 5310-01-509-5684

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-509-5684 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.194 inches nut and 0.405 inches nut **Overall Height:** 0.405 inches **Mounting Hole Diameter:** 0.098 inches **Nut Style:** Plate **Nut Length:** 0.840 inches **Nut Height:** 0.268 inches **Plate Thickness:** 0.030 inches Plate Width: 0.443 inches **Nut Counterbore Depth:** 0.070 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center:** Between 0.290 inches and 0.300 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.588 inches and 0.592 inches **Tempurature Rating:** Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit **Thread Series:** Unjc Thready Qty Per Inch (tpi):

**Features Provided:** Floating nut 32 **Thread Size:** 0.164 inches

## NSN 5310-01-509-5684

Plate Self-locking Nut - Page 2 of 2

Mil-std (military Standard):

Mil-r-6855 spec.



Special Features:
Steel nut, shell and washer; fuel resistant seal (350 degrees); dry film lubricant
Material:
Steel washer
Material Specification:
Mil-r-6855, cl 1, grade 60 military specification 1st material response seal
Surface Treatment:
Cadmium shell
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification 2nd treatment response shell
Specification Data:
80205-nas1474 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0