## NSN 5310-01-509-9071

Flat Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-509-9071

| Rectangular  Hole Diameter:  |
|--|
| Hole Diameter:   |
| Tiolo Piditiotori  |
| Between 0.255 inches and 0.275 inches  |
| Edge Shape:  |
| Square   |
| Center Hole Shape:   |
| 1 round  |
| Thickness:   |
| 0.090 inches   |
| End Application:   |
| F18 e/f  |
| Width Across Flats:  |
| Between 0.510 inches and 0.570 inches  |
| Criticality Code Justification:  |
| Agav   |
| Special Features:  |
| Primer - mil-prf-85582, type 1, class 1a or 1b; 2 coats of primer; parts manufactured from sheet or plate may be chamfered in lieu of radi |
| Material:  |
| Steel comp 301 or steel comp 321 or steel comp 347   |
| Material Specification:  |
| Mil-s-5059 military specification 1st material response or ams5510 assn standard 2nd material response or ams5512 assn standard 3rd        |
| material response  |
| Surface Treatment:   |
| Passivate and primer   |
| Specification Data:  |
| 70205-nas1401 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A022b0   |
| Mil-std (military Standard):   |
| Mil-s-5059 spec.   |