## NSN 5310-01-510-1168

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-510-1168 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.317 inches second end **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches **Nut Style:** Plate (floating) **Nut Length:** 1.292 inches **Nut Height:** 0.899 inches **Plate Thickness:** Between 0.035 inches and 0.045 inches Plate Width: 0.643 inches **Nut Counterbore Depth:** 0.625 inches second end **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.995 inches and 1.005 inches **End Application:** F-22 aircraft **Tempurature Rating:** 400.0 degrees celsius **Thread Series:** Unjf Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches

Material:

Steel comp xm-28 clip

**Material Specification:** 

Astm a313, type xm-28, armconitronic 32 assn standard single material response clip

## NSN 5310-01-510-1168

Plate Self-locking Nut - Page 2 of 2



Surface Treatment:
Passivate shell
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response shell
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0

Mil-s-5002 spec.

Mil-std (military Standard):