NSN 5310-01-519-9217

Plate Self-locking Nut - Page 1 of 2

Thread Direction:



View Online at https://aerobasegroup.com/nsn/5310-01-519-9217

| Right-hand |
|--|
| Locking Feature: |
| Prevailing torque with nonmetallic insert |
| Mounting Hole Diameter: |
| Between 2.4 millimeters and 2.6 millimeters |
| Nut Style: |
| Plate (floating) |
| Nut Height: |
| 12.7 millimeters |
| Plate Thickness: |
| Between 0.5 millimeters and 0.7 millimeters |
| Plate Width: |
| 14.6 millimeters |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Provision Location: |
| Opposite nut projection side |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Center To Center Distance Between Mounting Holes Along Length: |
| Between 17.4 millimeters and 17.5 millimeters |
| Tempurature Rating: |
| 232.0 degrees celsius |
| Thread Series: |
| Mj |
| Thread Size: |
| 5.0 millimeters |
| Thread Pitch In Millimeters: |
| 0.80 |
| Material: |
| Steel comp 316 nut |
| Material Specification: |
| Qq-s-763 federal specification single material response nut |
| Precious Material And Location: |
| Surface of nut and basket silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver shell |
| Surface Treatment Specification: |
| Ams2410 assn standard single treatment response nut |

NSN 5310-01-519-9217

Plate Self-locking Nut - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A021a0 | |

Mil-std (military Standard):

Shelf Life:

Mil-r-46198 spec.