

View Online at <https://aerobasegroup.com/nsn/5310-01-542-5929>

**Thread Direction:**

Left-hand

**Flange Thickness:**

0.184 inches

**Drive Point Depth:**

0.188 inches

**Nut Style:**

Round

**Nut Diameter:**

3.161 inches

**Nut Thickness:**

0.344 inches

**Drive Point Width:**

0.250 inches

**Undercut Thickness:**

0.080 inches

**Drive Point Quantity:**

8

**Hardness Rating:**

Between 26.0 rockwell c and 33.0 rockwell c

**Bearing Surface Finish:**

63.0 microinches

**Product Name:**

Locknut, sta-lok bearing retaining

**Special Features:**

1.5 millimeter (mm) pitch, 5 mm thread length, inside diameter 70 mm; finish is black oxide; one hole 0.047 on one tab, 0.055 from end

**Material:**

Steel comp 4130

**Material Specification:**

Ams-s-6758 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-stl-13924 cl 1, plus mil-prf-16173 gr 3 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-stl-13924 spec.