

View Online at <https://aerobasegroup.com/nsn/5310-01-585-5558>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

1.051 inches

**Nut Height:**

0.250 inches

**Plate Thickness:**

0.032 inches

**Plate Width:**

Between 0.290 inches and 0.422 inches

**Nut Mounting Provision:**

Countersunk holes

**Mounting Provision Location:**

Opposite nut projection side

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.339 inches and 0.349 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.310 inches and 0.314 inches

**Temperature Rating:**

800.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

49.0 rockwell c

**Thread Size:**

0.190 inches

**Mounting Hole Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

**Product Name:**

Nut, self-locking, plate, one lug, floating, low height, cres, 125 ksi ftu, 800 degrees f

**Material:**

Stainless steel

**Material Specification:**

Ams 5732 assn standard single material response or ams 5737 assn standard single material response or ams 5525 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0