Blind Rivet Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-586-2767

30FighenalRighenalRighenalBiplicationtersumkHand Style:1 BiplicationtersumkHand Right:0 Soli nobesHording Graup all metal designHording Graup all metal design all metal	Thread Class:
Right-hand Head Style: Eliptical countersunk Head Height: 0.058 inches Cocking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.773 inches and 0.797 inches Head Minor Diameter: 0.655 mils Cocking Feature: Dy film lubricant Nut Style: Bitter wirdsmooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Diameter: Between 1.039 inches and 1.869 inches Nut Clarget Between 1.039 inches and 1.869 inches Nut Gring Pange: 0.900/1.000 inches Shank End Type: Opgon Thread Series: Urif Thread Series: Opto 1.90 Dinels Between 50.0 degrees and 61.0 degrees Head Minor Countersink Angle: Discoundersink Angle: Discoundersink Angle: Discoundersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: </td <td>3b</td>	3b
Head Style: Eliptical countersumk Head Height: 0.058 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.773 inches and 0.797 inches Head Minor Diameter: 0.655 mills Lubrication: Dy film lubricant Nut Style: Bilm rivet wismooth round shank Nut Longth: Between 0.612 inches and 0.614 inches Nut Length: Between 0.613 inches and 1.869 inches Nut Longth: Between 0.614 inches 9.990/+1.000 inches Shank End Type: 0.990 Opin Chead Steice: 0.012 0.990 Thread Series: Unjf Thread Series: 0.010 inches Shank End Type: 0.900 10.010 inches Stank End Type: 0.901 10.010 inches 10.010 inches 10.010 inches 10.010 inches 10.010 in	Thread Direction:
Eliptical countersumk Head Height: 0.058 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.773 inches and 0.797 inches Head Major Diameter: 0.655 mils Lubrication: Nut Style: Bill rivet wismooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Longth: Between 0.839 inches and 1.869 inches Nut Grig Rage: +0.990/+1.000 inches Shank End Type: Open Thread Series: Urig Thread Series: Opin Cheed Size: 0.500 inches Head Major Countersink Angle: Between 5.0.0 degrees and 61.0 degrees Head Series: Opin Thread Series: Discountersink Angle: Between 5.0.0 degrees and 61.0 degrees Head Moor Countersink Angle: Between 5.0.0 degrees and 7.0 degrees Head Series: Between 5.0.0 degrees and 7.0 degrees Head	Right-hand
Eliptical countersumk Head Height: 0.058 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.773 inches and 0.797 inches Head Major Diameter: 0.655 mils Lubrication: Nut Style: Bill rivet wismooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Longth: Between 0.839 inches and 1.869 inches Nut Grig Rage: +0.990/+1.000 inches Shank End Type: Open Thread Series: Urig Thread Series: Opin Cheed Size: 0.500 inches Head Major Countersink Angle: Between 5.0.0 degrees and 61.0 degrees Head Series: Opin Thread Series: Discountersink Angle: Between 5.0.0 degrees and 61.0 degrees Head Moor Countersink Angle: Between 5.0.0 degrees and 7.0 degrees Head Series: Between 5.0.0 degrees and 7.0 degrees Head	Head Style:
0.058 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.773 inches and 0.797 inches Head Minor Diameter: 0.655 mils Lubrication: Dy film lubricant Nut Style: Bild rivet wismooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Length: Between 0.613 inches and 0.614 inches Nut Cip Range: +0.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.00 degrees fahrenheit Thread Series: Unjf Thread Series: 0.500 inches Head Major Countersink Angle: Between 55.0 degrees and 61.0 degrees Head More Countersink Angle: Between 55.0 degrees and 75.0 degrees Head More Countersink Angle: Between 55.0 degrees and 75.0 degrees Head More Countersink Angle: Between 55.0 degrees and 75.0 degrees Head More Countersink Angle: Between 55.0 degrees and 75.0 degrees <td< td=""><td></td></td<>	
Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.773 inches and 0.797 inches Head Minor Diameter: 0.655 mils Lubrication: Dyr flin lubricant Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Logneter: Between 1.839 inches and 1.869 inches Nut Crip Range: +0.990/+1.000 inches Shank End Type: Open Thread Series: Unjf Thread Series: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 59.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Hordux Imae: Nut, self-locking, blind rivet, elliptical head, 450 degrees f	Head Height:
Prevail Prevail <td< td=""><td>0.058 inches</td></td<>	0.058 inches
Head Major Diameter: Between 0.773 inches and 0.797 inches Head Minor Diameter: 0.655 mils Lubrication: Dy fin lubricant Nut Style: Bind rivet wismooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Length: Between 1.839 inches and 0.614 inches Nut Crip Range: +0.990/+1.000 inches Shark End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Stries: Unf Finead Stries: 0.001 inches Between 50.0 degrees and 61.0 degrees Head Major Countersink Angle: Between 50.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 50.0 degrees and 76.0 degrees	Locking Feature:
Head Major Diameter: Between 0.773 inches and 0.797 inches Head Minor Diameter: 0.655 mils Lubrication: Dy fin lubricant Hustration: Dy fin lubricant Nut Style: Bind rivet w/smooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Carghe: Between 1.839 inches and 0.614 inches Nut Carghe: 4.0.990/+1.000 inches Shank End Type: Open Stenker Atting: 40.990 /+1.000 inches Shank End Type: Open Thread Series: Unjf Thread Series: Uojf Thread Strie 0.00 inches Hadajor Countersink Angle: Between 5.0 degrees and 6.0 degrees 1 Between 5.0 degrees and 7.0 degrees Head Minor Countersink Angle: Between 5.0 degrees and 7.0 degrees Head Minor Countersink Angle: Between 5.0 degrees and 7.0 degrees Head Minor Countersink Angle: Between 5.0 degrees and 7.0 degrees	Prevailing torque all metal design
Head Minor Diameter: 0.655 mils Lubrication: Dry film lubricant Nut Style: Bind rivet w/smooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Diameter: Between 1.839 inches and 1.869 inches Nut Grip Range: 40.990/41.000 inches Shank End Type: Open Tenpurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thread Size: 0.500 inches Between 55.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees	
0.655 milsLubrication:Dry film lubricantNut Style:Bind rivet w/smooth round shankNut Diameter:Between 0.612 inches and 0.614 inchesNut Length:Between 1.839 inches and 1.869 inchesNut Grip Range:+0.990/+1.000 inchesShank End Type:OpenTemparature Rating:450.0 degrees fahrenheitThread Series:UnjfThread Series:0.500 inchesHat Major Countersink Angle:0.500 inchesHead Mior Countersink Angle:Between 75.0 degrees and 76.0 degreesFredu King, blind rivet, elliptical head, 450 degrees faNut, self-locking, blind rivet, elliptical head, 450 degrees faSpecial Features:	Between 0.773 inches and 0.797 inches
Lubrication: Dry film lubricant Nut Skyle: Blind rivet w/smooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Length: Between 1.839 inches and 1.869 inches Nut Grip Range: +0.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thread Stize: 0.500 inches Head Major Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees fa Special Features:	Head Minor Diameter:
Dry film lubricant Nut Style: Bind rivet wismooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Length: Between 1.839 inches and 0.614 inches Nut Grip Range: 40.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 76.0 degrees Froduct Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees fa	0.655 mils
Nut Style: Bind rivet w/smooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Length: Between 1.839 inches and 1.869 inches Nut Grip Range: +0.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unif Thready Qty Per Inch (tpi): 20 Hard Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees fl	Lubrication:
Nut Style: Bind rivet w/smooth round shank Nut Diameter: Between 0.612 inches and 0.614 inches Nut Length: Between 1.839 inches and 1.869 inches Nut Grip Range: +0.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unif Thready Qty Per Inch (tpi): 20 Hard Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees fl	Dry film lubricant
Nut Diameter:Between 0.612 inches and 0.614 inchesNut Length:Between 1.839 inches and 1.869 inchesNut Grip Range:+0.990/+1.000 inchesShank End Type:OpenTempurature Rating:450.0 degrees fahrenheitThread Series:UnjfThread Syley Per Inch (tpi):20Thread Size:0.500 inchesHead Major Countersink Angle:Between 59.0 degrees and 76.0 degreesPreduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees faSpecial Features:	Nut Style:
Between 0.612 inches and 0.614 inches Nut Length: Between 1.839 inches and 1.869 inches Nut Grip Range: 40.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thread Size: 0.500 inches Head Major Countersink Angle: Between 5.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Froduct Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f	Blind rivet w/smooth round shank
Nut Length: Between 1.839 inches and 1.869 inches Nut Grip Range: +0.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thread Syries: 0.500 inches Between 59.0 degrees and 61.0 degrees Head Major Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f	Nut Diameter:
Between 1.839 inches and 1.869 inchesNut Grip Range:+0.990/+1.000 inchesShank End Type:OpenTempurature Rating:450.0 degrees fahrenheitThread Series:UnjfThready Qty Per Inch (tpi):20Thread Size:0.500 inchesHead Major Countersink Angle:Between 75.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees faSpecial Features:	Between 0.612 inches and 0.614 inches
Nut Grip Range:+0.990/+1.000 inchesShank End Type:OpenTempurature Rating:450.0 degrees fahrenheitThread Series:UnjfThready Qty Per Inch (tpi):20Thread Size:0.500 inchesHead Major Countersink Angle:Between 59.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees fSpecial Features:	Nut Length:
+0.990/+1.000 inches Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unif Thread Series: Unif Thready Qty Per Inch (tpi): 20 Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Nut, self-locking, blind rivet, elliptical head, 450 degrees f	Between 1.839 inches and 1.869 inches
Shank End Type: Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thready Qty Per Inch (tpi): 20 Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees	Nut Grip Range:
Open Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 20 Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	+0.990/+1.000 inches
Tempurature Rating:450.0 degrees fahrenheit450.0 degrees fahrenheitThread Series:UnifThready Qty Per Inch (tpi):20Thread Size:0.500 inchesHead Major Countersink Angle:Between 59.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees fSpecial Features:	Shank End Type:
450.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 20 Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees	Open
Thread Series:UnjfThready Qty Per Inch (tpi):20Thread Size:0.500 inchesHead Major Countersink Angle:Between 59.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees fSpecial Features:	Tempurature Rating:
Unjf Thready Qty Per Inch (tpi): 20 Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Hout, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	450.0 degrees fahrenheit
Thready Qty Per Inch (tpi):20Thread Size:0.500 inchesHead Major Countersink Angle:Between 59.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees fSpecial Features:	Thread Series:
20 Thread Size: 0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	Unjf
Thread Size:0.500 inchesHead Major Countersink Angle:Between 59.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees fSpecial Features:	Thready Qty Per Inch (tpi):
0.500 inches Head Major Countersink Angle: Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	20
Head Major Countersink Angle:Between 59.0 degrees and 61.0 degreesHead Minor Countersink Angle:Between 75.0 degrees and 76.0 degreesProduct Name:Nut, self-locking, blind rivet, elliptical head, 450 degrees fSpecial Features:	Thread Size:
Between 59.0 degrees and 61.0 degrees Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	0.500 inches
Head Minor Countersink Angle: Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	Head Major Countersink Angle:
Between 75.0 degrees and 76.0 degrees Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	Between 59.0 degrees and 61.0 degrees
Product Name: Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	Head Minor Countersink Angle:
Nut, self-locking, blind rivet, elliptical head, 450 degrees f Special Features:	Between 75.0 degrees and 76.0 degrees
Special Features:	Product Name:
	Nut, self-locking, blind rivet, elliptical head, 450 degrees f
Dry film lube on threads only; tensile strength 21, 110 lbs min; torque out in 860 lbs min; push out 2, 280 lbs min	Special Features:
	Dry film lube on threads only; tensile strength 21, 110 lbs min; torque out in 860 lbs min; push out 2, 280 lbs min

NSN 5310-01-586-2767

Blind Rivet Self-locking Nut - Page 2 of 2



Material:

Steel comp 304 and steel comp 305

Material Specification:

Qq-s-763, cond a type 304 federal specification single material response or qq-s-763, cond a type 305 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0