

View Online at <https://aerobasegroup.com/nsn/5310-01-586-3117>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Head Style:**

Elliptical countersunk

**Head Height:**

0.034 inches

**Locking Feature:**

Prevailing torque all metal design

**Head Major Diameter:**

Between 0.310 inches and 0.332 inches

**Head Minor Diameter:**

0.257 mils

**Lubrication:**

Dry film lubricant

**Nut Style:**

Blind rivet w/smooth round shank

**Nut Diameter:**

Between 0.239 inches and 0.241 inches

**Nut Length:**

Between 0.150 inches and 0.180 inches

**Nut Grip Range:**

+0.080/+0.100 inches

**Shank End Type:**

Closed

**Temperature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unf

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Head Major Countersink Angle:**

Between 75.0 degrees and 77.0 degrees

**Head Minor Countersink Angle:**

Between 59.0 degrees and 61.0 degrees

**Product Name:**

Nut, self-locking, blind rivet, elliptical head, closed end, 450 degrees f

**Special Features:**

Dry film lube on threads only per mil-n-25027; tensile strength 2, 650 lbs min; torque out in 60 lbs min; push out 150 lbs min

**Material:**

Steel comp 304 or steel comp 305

**Material Specification:**

Qq-s-763, cond a type 304 federal specification single material response or qq-s-763, cond a type 305 federal specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii class 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0