
Blind Rivet Self-locking Nut - Page 1 of 2





Thread Class: 3b **Thread Direction: Right-hand** Head Style: Eliptical countersunk **Head Height:** 0.034 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.310 inches and 0.332 inches **Head Minor Diameter:** 0.257 mils Lubrication: Dry film lubricant Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.239 inches and 0.241 inches Nut Length: Between 0.150 inches and 0.180 inches Nut Grip Range: +0.080/+0.100 inches Shank End Type: Closed **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unf Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Head Major Countersink Angle: Between 75.0 degrees and 77.0 degrees Head Minor Countersink Angle: Between 59.0 degrees and 61.0 degrees **Product Name:** Nut, self-locking, blind rivet, elliptical head, closed end, 450 degrees f **Special Features:**

Dry film lube on threads only per mil-n-25027; tensile strength 2, 650 lbs min; torque out in 60 lbs min; push out 150 lbs min

NSN 5310-01-586-3117

Blind Rivet Self-locking Nut - Page 2 of 2



Material:

Steel comp 304 or steel comp 305

Material Specification:

Qq-s-763, cond a type 304 federal specification single material response or qq-s-763, cond a type 305 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0