Gang Channel Self-locking Nut - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5310-01-607-8859

Tread Dress: 3b Thread Drection: Right-hand Locking Feature: Free-running all metal design Nut Style: A20 gang channel, sell locking Base Witch: A20 gang channel, sell locking Base Witch: A20 inches Nut Length: 7.20 inches Base Thickness: A055 inches Statistical design Nut Height: A23 inches End Application: E-3 block 404 Tempurature Rating: 250 dogrees fahrenheit Thread Series: Unif Thread Series: A30 ockwell c Thread Size:	
Right-hand Right-hand Locking Feature: Free-running all metal design Mut Style: 20 gang channel, self locking Base With: 0.726 inches 0.726 inches 7.20 inches 2.01 chans 2.02 inches 2.02 inches 2.02 inches 2.03 inches 2.03 inches 2.04 chanse 2.03 inches 2.03 inches 2.04 chanse 2.03 inches 2.04 chanse 2.04 chanse 2.05 degrees tharehabet 2.05 degrees tharehabet 2.05 degrees tharehabet 2.04 chanse Rating: 2.05 degrees tharehabet 2.04 degrees tharehabet 2.04 degrees tharehabet 2.04 degrees tharehabet 2.05 degrees tharehabet	Thread Class:
Right-hand Locking Feature: Free-running all metal design Nut Style: A20 gang dhannel, self locking Base Nickine: 0.726 inches Base Thickness: 0.326 inches 1.326 inches 0.326 inches 0.326 inches 2.302 degrees fahrenheit Thread Vary Per Inch (pt): 2.4 Hardness Rating: 0.3125 inches 2.3126 inches 2.3126 inches 1.3126 inches 2.3127 inches 1.3126 inches 2.3128 inches 1.3126 inches 2.3128 inches 1.3128 inches 2.3128 inches 3.3128 inches	
Loking Feature: Free-running all metal design Nut Style: A20 gang channel, self locking Base Widt: 0.726 inches Nut Longth: 0.726 inches Nut Longth: 0.726 inches Base Widt: 0.726 inches Base Thickness: 0.510 inches 0.525 inches Base Thickness: 0.528 inches Pathetiste: 0.528 inches Pathetiste: 0.528 inches Pathetiste: 0.538 inches Pathetiste: 0.500 degrees fahrenheit Pathetiste: 0.500 degrees fahrenheit Pathetiste: 0.500 degrees fahrenheit Pathetiste: 1016 Pathetiste: 1026 10372 inches 20302 inches 20302 inches 20312 inches 2032 inches 2032 inches 2032 inches 2032 inches 2032 inches <t< td=""><td></td></t<>	
Free-running all metal design Nu Style: A20 gang channel, sell locking Base With: 0.726 inches 0.726 inches 720 inches Base Thickness: 0.55 inches 0.55 inches 0.55 inches 0.55 inches 0.52 inches 0.53 inches Data Thickness: 0.53 inches Data Thickness: 0.53 inches E-3 block 404 Tomparture Rating: 250 odgrees fahrenheit Thread Series: Unif Thread Series: 0.71 Order Series 0.72 inches 0.72 inches 0.73 inches 0.73 inches 0.74 etement spacing = 0.875. Maximum number of nut elements = 82 Material: Second 1035 nut Shift Life: Na National Second 1035 nut Shift Life: National Second 1035 nut Shift Life: National Second 1035 nut Shift Life: Natorial:	
Nut Style: A20 gang channel, self locking Base With: 0.726 inches 0.726 inches 72.0 inches Base Thickness: 2.0.1000 Base Thickness: 0.55 inches Base Thickness: 0.55 inches Bate Thickness: 0.55 inches Bate Statistic Bate Statistic </td <td></td>	
A20 gang channel, self locking Base Width: 0.726 inches Nut Length: 2.0 inches Base Thickness: 0.55 inches 0.55 inches Nut Height: 0.328 inches End Application: 2.3 block 404 Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Urif Hardens Rating: 40.0 rockwell c Hardens Rating: 0.325 inches Solo degrees fahrenheit Hordens Rating: 0.3125 inches 9.0 rockwell c Hardens Rating: 0.3125 inches Solot Fostures: 0.3125 inches Stel comp 1035 nut Babertie: Nut element spacing =0.875. Maximum number of nut elements = 82 Materia: Stel comp 1035 nut Shelf Life: Na Diff Measure: Na Stel comp 1035 nut Stel comp 1035 nut Stel comp 1035 nut Stel comp 1035	
Base Width: 0.726 inches Nut Length: 720 inches 720 inches Base Thickness: 0.55 inches 0.55 inches 0.55 inches 0.40 Height: 0.328 inches E-3 block 404 Tompurature Rating: 25.00 degrees fahrenheit Thready Objer Einch (rgh): 24 Marting: 240 rockwell c Thready Objer Einch (rgh): 24 Parlenses 25.01 rockwell c Nut Height: 20.02 rockwell c Thread Size: 20.12 rockwell c Size inches Nut element spacing =0.875. Maximum number of nut elements = 82 Matrial: Nut element spacing =0.875. Maximum number of nut elements = 82 Matrial: Nut element spacing =0.875. Maximum number of nut elements = 82 Matrial: Nut element spacing =0.875. Maximum number of nut elements = 82 Matrial: Nut element spacing =0.875. Maximum number of nut elements = 82 Matrial: Nut element sp	
0.726 linchesNut Lengti:7.20 linchesBase Thickness:0.58 linches0.58 linchesNut Height:0.328 linchesEnd Application:2.328 linches2.50 degrees fahrenheit7.50 degrees fahrenheit2.50 degrees fahrenheitThread Series:Unif7.51 deck Well C2.62 linches2.72 linches2.81 ment spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Nut element spacing = 0.875. Maximum	A20 gang channel, self locking
Nu Length: 72.0 inches Base Thickness: 0.55 inches Nut Height: 0.320 inches Parlation: 2.3 block 404 Tempuration: 2.4 block 404 Tempuration: 2.5 block 404 Tempuration: 2.5 block 404 Tempuration: 2.6 block 404 Thread Series: 2.7 block 405 Parlead State: 3.0 cockwell o Thread Size: 0.3125 inches Secial Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Stel comp 1035 nut Shell Heil: Na Child Measure: Na Material: Na L	Base Width:
72.0 inches Base Thickness: 0.5.5 inches Nut Height: 0.328 inches Endaplication: Fabload Add Tempurature Rating: 25.0.0 degrees fahrenheit 7.0.0 degrees fahrenheit Thread Series: 20.1.0 degrees fahrenheit 7.0 more Rating: 20.0 degrees fahrenheit Thread Series: 20.1.0 degrees fahrenheit 1.0 degrees fahrenheit 9.0 degrees fahrenheit 9.0 degrees fahrenheit 1.0 degrees fahrenheit 9.0 degrees fahrenheit <t< td=""><td>0.726 inches</td></t<>	0.726 inches
Base Thickness: 0.55 inches Nur Height: 0.328 inches End Application: E-3 block 404 Tempurature Rating: 230 od greese fahrenheit Thread Series: Od greese fahrenheit Thread Series: Volt Part Inch (tpi): 24 Hardness Rating: 49.0 rockwell c Thread Size: 0.3125 inches Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Stee comp 1035 nut Shef Life: Na Uht Of Messure: Na Dinditrizzation: Fore Family The State: Na Na Company Na Company Steel Comp 1035 nut Steel Comp 1035 nut <t< td=""><td>Nut Length:</td></t<>	Nut Length:
0.55 inchesNut Height:0.328 inchesEnd Application:E-3 block 404Tempurature Rating:250.0 degrees fahrenheitThread Series:UnjfThread Qt Per Inch (tpi):24Hardness Rating:49.0 rockwell cThread Size:0.3125 inchesSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Stoel Comp 1035 nutShelf Life:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Stoel Comp 1035 nutShelf Life:NaUnit of Measure:NaNut element spacing =0.875. Maximum number of nut elements = 82Material:NaNaUnit of Measure:NaNaNaStoel Comp 1035 nutStoel Comp 1035 nutSto	72.0 inches
Nut Height:0.328 inchesEnd Application:E-3 block 404Tempurature Rating:250.0 degrees fahrenheitThread Series:UnjfThready Oty Per Inch (tpl):24Hardness Rating:0.3 to ckwell cThread Size:0.3 to ckwell cSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Materiat:Stel comp 1035 nutStel furge:Nut element spacing =0.875. Maximum number of nut elements = 82Materiat:Stel comp 1035 nutStel comp 1035 nutSt	Base Thickness:
0.328 inchesEnd Application:E-3 block 404Tempurature Rating:250.0 degrees fahrenheitThread Series:UnjfThready Oty Per Inch (tpi):24Hardness Rating:49.0 rockwell cThread Size:0.3125 inchesSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutSheft Life:NaDird Measure:NaThe Company Comp	0.55 inches
Erd Application: E-3 block 404 Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: 49.0 rockwell c Thread Size: 0.3125 inches Special Features: Nut element spacing = 0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Sheff Life: Na Did Measure: T Paniliarization: No Fig:	Nut Height:
E3 block 404Tempurature Rating:250.0 degrees fahrenheitThread Series:UnjfThready Qty Per Inch (tpi):24Hardness Rating:49.0 rockwell cThread Size:0.3125 inchesSpecial Features:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutSheff Life:NaUnit of Measure:-Denilitarization:NaFig:Fig:	0.328 inches
Tempurature Rating:250.0 degrees fahrenheitThread Series:UnjfThready Qty Per Inch (tpi):24Hardness Rating:49.0 rockwell cThread Size:0.3125 inchesSpecial Features:Nut element spacing = 0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutSheif Life:NaUnit Of Measure:Denilitarization:NoFig:Fig:	End Application:
250.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: 49.0 rockwell c Thread Size: 0.3125 inches 3.125 inches 3.125 inches Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Stel comp 1035 nut Stel comp 1035 nut Stel Comp 1035 nut Stel Comp 1035 nut Thread Size: Na Stel Comp 1035 nut Stel Comp 1035 nut	E-3 block 404
Thread Series:UnjfThready Qty Per Inch (tpi):2424Hardness Rating:49.0 rockwell cThread Size:0.3125 inchesSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutShelf Life:NaUnit Of Measure:Penilitarization:NoFig:	Tempurature Rating:
Unif Thready Qty Per Inch (tpi): 24 Hardness Rating: 49.0 rockwell c Thread Size: 0.3125 inches Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Shelf Life: N/a Ditt Of Measure: Femilitarization: No Fig:	250.0 degrees fahrenheit
Thready Qty Per Inch (tpi):2424Hardness Rating:49.0 rockwell cThread Size:0.3125 inchesSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutShelf Life:N/aUit Of Measure:-Demilitarization:NoFig:	Thread Series:
24 Hardness Rating: 49.0 rockwell c Thread Size: 0.3125 inches 0.3125 inches Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Steel comp 1035 nut Steel comp 1035 nut Unit Of Measure: - - Demiltarization: No	Unjf
Hardness Rating:49.0 rockwell cThread Size:0.3125 inches0.3125 inchesSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutShelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	Thready Qty Per Inch (tpi):
49.0 rockwell c Thread Size: 0.3125 inches Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Shelf Life: N/a Unit Of Measure: Fmilitarization: No	24
Thread Size:0.3125 inchesSpecial Features:Nut element spacing =0.875. Maximum number of nut elements = 82Material:Steel comp 1035 nutShelf Life:N/aN/aDint Of Measure:Demilitarization:NoFig:	Hardness Rating:
0.3125 inches Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Steel comp 1035 nut Stee	49.0 rockwell c
Special Features: Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Size:
Nut element spacing =0.875. Maximum number of nut elements = 82 Material: Steel comp 1035 nut Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.3125 inches
Material:Steel comp 1035 nutShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Special Features:
Steel comp 1035 nut Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Nut element spacing =0.875. Maximum number of nut elements = 82
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
N/a Unit Of Measure: Demilitarization: No	Steel comp 1035 nut
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A021a0	Fiig:
	A021a0