

View Online at <https://aerobasegroup.com/nsn/5315-00-001-2297>

Shank Diameter:

Between 0.4345 inches and 0.4360 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.500 inches and 1.520 inches

Actuation Type:

Push

Hardness Rating:

58.0 rockwell c detent and 62.0 rockwell c detent

Shear Strength:

25000 double pounds per square inch

Shoulder To Head End Distance:

1.470 inches

Pin Center To Handle End Distance:

1.775 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.350 inches and 0.380 inches

Special Features:

Attaching hook or ring, steel qq-w-428 or cres qq-w-423 comp 302 with cadmium qq-p-416 type 1 or 2, cl 3 or passivate qq-p-35 surface

Material:

Steel spring

Material Specification:

Qq-w-470 federal specification single material response spring

Surface Treatment:

Passivate detent

Surface Treatment Specification:

Qq-p-416, type 1 or 2, cl 3 federal specification 1st treatment response collar or qq-p-35 federal specification 2nd treatment response collar

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.