## NSN 5315-00-001-5113

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-001-5113 **Head Diameter:** 1.390 inches **Shank Diameter:** Between 0.9960 inches and 0.9990 inches **Ring Handle Diameter:** 2.300 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 3.600 inches and 3.620 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature **Hardness Rating:** 54.0 rockwell c detent and 64.0 rockwell c detent **Shear Strength:** 131000 double pounds per square inch **Shoulder To Head End Distance:** 3.020 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 1.100 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1363 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5315-00-001-5113

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.