

View Online at <https://aerobasegroup.com/nsn/5315-00-003-3919>

**Head Style:**

Pan no. 2 (r1 not required in item description)

**Diameter:**

Between 0.123 inches and 0.124 inches

**Under Head Length:**

0.699 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.042 inches and 0.047 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.074 inches

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Pin Head Diameter:**

0.188 inches

**Surface Finish:**

32.0 microinches outside diameter

**Height:**

0.047 inches

**Material:**

Steel comp 630

**Material Specification:**

Ams fscm 81343 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Straight

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.