

View Online at <https://aerobasegroup.com/nsn/5315-00-003-3929>

**First End Style:**

Countersunk

**Inside Diameter:**

Between 1.0620 inches and 1.0625 inches

**Pinlength:**

Between 2.240 inches and 2.245 inches

**Pindiameter:**

Between 1.8740 inches and 1.8743 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Criticality Code Justification:**

Achu and aarx

**First End Countersink Angle:**

60.0 degrees

**First End Countersink Diameter:**

1.122 inches

**Material:**

Steel comp xm-12

**Material Specification:**

Ams5659 fscm 26512 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.