

View Online at <https://aerobasegroup.com/nsn/5315-00-003-3929>

First End Style:

Countersunk

Inside Diameter:

Between 1.0620 inches and 1.0625 inches

Pinlength:

Between 2.240 inches and 2.245 inches

Pindiameter:

Between 1.8740 inches and 1.8743 inches

Second End Relationship With First End:

Identical

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Criticality Code Justification:

Achu and aarx

First End Countersink Angle:

60.0 degrees

First End Countersink Diameter:

1.122 inches

Material:

Steel comp xm-12

Material Specification:

Ams5659 fscm 26512 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.