

View Online at <https://aerobasegroup.com/nsn/5315-00-003-6713>

**Head Diameter:**

Between 0.640 inches and 0.755 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Helicopter, lamps mark iii, sh-60b; ta-4j aircraft; aircraft, viking s-3b; helicopter, seasprite h-2; helicopter, utility/search and recovery uh-1n; aircraft, hornet f/a-18; aircraft, tomcat f-14; helicopter, sea king h-3; helicopter, carrier based asw, sh-60f

**Grip Length:**

Between 1.500 inches and 1.520 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.070 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

Between 0.540 inches and 0.590 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0