

View Online at <https://aerobasegroup.com/nsn/5315-00-003-6713>

Head Diameter:

Between 0.640 inches and 0.755 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Helicopter, lamps mark iii, sh-60b; ta-4j aircraft; aircraft, viking s-3b; helicopter, seasprite h-2; helicopter, utility/search and recovery uh-1n; aircraft, hornet f/a-18; aircraft, tomcat f-14; helicopter, sea king h-3; helicopter, carrier based asw, sh-60f

Grip Length:

Between 1.500 inches and 1.520 inches

Actuation Type:

Pull and push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.070 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.540 inches and 0.590 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0