

View Online at <https://aerobasegroup.com/nsn/5315-00-006-0919>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.370 inches and 0.420 inches

**Pinlength:**

Between 1.250 inches and 1.280 inches

**Pindiameter:**

Between 0.1800 inches and 0.1900 inches

**Second End Slot Width:**

Between 0.060 inches and 0.070 inches

**First End Taper Length:**

Between 0.060 inches and 0.080 inches

**Second End Slot Depth:**

0.125 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.190 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Pin Grip Length:**

Between 0.980 inches and 1.000 inches

**Surface Finish:**

125.0 microinches

**Material:**

Steel

**Material Specification:**

Sae 1010 through 1020 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-13924 spec.