## NSN 5315-00-007-2981

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-007-2981 **Head Diameter:** 0.940 inches Handle Length: Between 2.180 inches and 2.500 inches Shank Diameter: Between 0.497 inches and 0.4995 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 1.000 inches and 1.020 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature **Hardness Rating:** 54.0 rockwell c detent and 64.0 rockwell c detent **Shoulder To Head End Distance:** 2.180 inches Pin Attachment Type: Hook **Detent To Tapered End Distance:** 0.590 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator:** T handle **Specification Data:** 80205-nas1358 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5315-00-007-2981

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.