

View Online at <https://aerobasegroup.com/nsn/5315-00-007-6103>

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

Between 0.875 inches and 1.135 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

2w/s: emory s. Land class as; forrestal class cv; gun mount, mk 75 (gm); helicopter, mh-53e; support equipment, b-52 aircraft; oliver perry class ffg; engine, aircraft f110-ge-400; los angeles class ssn (688); virginia class submarine, ssn-774

Grip Length:

Between 1.600 inches and 1.620 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

Special Features:

Collar /1h/ is used only with aluminum handle

Material:

Steel comp 630 spindle

Material Specification:

Ams 5643 assn standard single material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0