

View Online at <https://aerobasegroup.com/nsn/5315-00-007-9851>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Pinlength:**

Between 1.240 inches and 1.260 inches

**Pindiameter:**

Between 0.3134 inches and 0.3136 inches

**First End Taper Length:**

Between 0.031 inches and 0.062 inches

**Second End Taper Length:**

0.035 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Shear Strength:**

11000 double pounds per square inch

**First End Taper Angle:**

Between 20.0 degrees and 30.0 degrees

**Second End Taper Angle:**

Between 4.0 degrees and 12.0 degrees

**Special Features:**

Small chamfer end may have 0.031 in. Min 0.062 in.Max radius in lieu of chamfer

**Material:**

Steel comp 410 or steel comp 416

**Material Specification:**

Fed standard 66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0