

View Online at <https://aerobasegroup.com/nsn/5315-00-009-0512>

**Head Diameter:**

Between 0.735 inches and 0.765 inches

**Shank Diameter:**

Between 0.620 inches and 0.623 inches

**Ring Handle Diameter:**

Between 1.500 inches and 1.687 inches

**Detent Quantity:**

2

**Grip Length:**

Between 4.400 inches and 4.420 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shoulder To Head End Distance:**

Between 0.380 inches and 0.560 inches

**Detent To Tapered End Distance:**

Between 0.612 inches and 0.672 inches

**Material:**

Steel comp 4130 shank

**Material Specification:**

Mil-s-6758 military specification single material response shank

**Surface Treatment:**

Cadmium shank and chromate shank

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response shank or mil-c-81562, type 2, cl 2 military specification single treatment response shank

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.