# NSN 5315-00-009-3894

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-009-3894

## Head Diameter:

Between 0.360 inches and 0.450 inches

## Shank Diameter:

Between 0.2470 inches and 0.2485 inches

## **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

## **Detent Quantity:**

2

## **Actuation Method:**

Push button

Grip Length:

Between 1.900 inches and 1.920 inches

## Actuation Type:

Pull and push

## Hardness Rating:

40.0 rockwell c spindle

## Shoulder To Head End Distance:

0.935 inches

## Pin Attachment Type:

Hook

## Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

## Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

Ring handle

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0