## NSN 5315-00-009-4760

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-009-4760

First End Style:
Slotted
Overall Length:
2.870 inches
Diameter:
Between 0.2492 inches and 0.2497 inches
Effective Length: 2.250 inches
Undercut Diameter:
0.195 inches
Undercut Width:
0.070 inches
Undercut Radius:
0.035 inches
Hole Arrangement Style:
Both end drilled
First Hole Diameter:
Between 0.077 inches and 0.082 inches
Second Hole Diameter:
Between 0.077 inches and 0.082 inches
Distance From Centerline Of Hole To End Of Pin:
0.138 inches
Center To Center Distance Between Holes:
2.594 inches
First End Slot Width:
0.050 inches
First End Slot Depth:
0.094 inches
Second End Relationship With First End:
Identical
Hardness Rating:
38.0 rockwell c and 44.0 rockwell c
First End Location:
Both ends
Surface Finish:
63.0 microinches
Special Features:
1/4-28 unf-2a threaded to grooves on both ends; holes drilled 90 degrees to slot both ends
Material:
Steel comp 4130
Material Specification:

Mil-s-6758, d4 military specification single material response

## NSN 5315-00-009-4760

Headless Grooved Pin - Page 2 of 2

A212a0

Mil-s-6758 spec.

Mil-std (military Standard):



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Style Designator:
Groove
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: